Supplying safety, welfare, site equipment, tools and engineering accessories





SUPPORTING CONSTRUCTION

NEV

INNOVATION

"Latest addition to our Constructor range - the Visilite illuminating Helmet Band"

Be seen

Order Codes: HA2VE1 - Visilite LED Lighting System to suit Evolite Helmet range

HA2VE3 - Visilite LED Lighting System to suit EVO 2/3/5 Helmet range





Enquire today. Contact OnSite Support on: 01293 744 444

T: 01293 744 444 E: sales.support@onsite-support.co.uk W: www.onsite-support.co.uk | ORDER ONLINE TODAY







Supplying safety, welfare, site equipment, tools and engineering accessories





SUPPORTING CONSTRUCTION




Visilite - Be seen



Standards, Testing & Performance	
Modes & Runtimes	Mode1: Static (9hrs) Mode2: Fast flash (150hrs) Mode3: Slow flash (190hrs)
Charge Time	Standard Charge: Approx 4.0 hours Fast Charge: Approx 2.5 hours
Operating Temperature Range:	+50°C to -10°C 14°F and 122°F
IP Rating	IP54





🌄 50m VISIBILITY

- Independently tested for luminous intensity, visibility in darkness & flash rate
- During optical testing Visilite[™] remained visible up to a distance of 50m.



 FLEXIBLE FIBRE OPTIC
 Ultra flexible, durable clear fibre optic withstands knocks and scrapes.



EASY SECURE FIT

- Simply clip onto the sides and rear of the safety helmet.
- Quick release for replacement or USB charging.



- DURABLE
 The clips and main housing are made from highly durable ABS.
- The main housing is sealed to protect against dust and dirt.



🗾 USB RECHARGEABLE

- Easily rechargeable with a USB charging supply; PC, Mains or Car.
- Can be charged while fitted to the helmet.
- Micro USB cable supplied.



 ✓ ADVERSE WEATHER
 Visilite[™] is splash proof making it suitable for use in wet weather conditions.

 It has an operating Temperature Range of: +50°C to -10°C (14°F and 122°F).







